

# Fabric specification

**Avelino**

|               |                        |
|---------------|------------------------|
| Fabric type   | Artificial leather     |
| Composition   | 85% PVC, 15% polyester |
| Weight (g/m²) | 450 ± 25% g/m²         |
| Width (cm)    | 140 ± 2cm              |

| TEST TYPES               | TEST METHOD | RESULT            |
|--------------------------|-------------|-------------------|
| Martindale abrasion      | ISO 12947-2 | > 100.000         |
| Seam slippage            | ISO 13936-2 | N/A               |
| Colour fastness dry/wet  | ISO 105-X12 | dry - 5 / wet - 5 |
| Colour fastness to light | ISO 105-B02 | 4/5               |
| Tear strength            | ISO 13937-3 | N/A               |
| Tensile strength         | ISO 13934-1 | N/A               |
| Pilling                  | ISO 12945-2 | N/A               |

|                                  |                        |
|----------------------------------|------------------------|
| OEKO-TEX® environmental standard | OEKO-TEX® STANDARD 100 |
| FR standards                     | BS5852 Source 0        |

| CARE INSTRUCTIONS         |             |
|---------------------------|-------------|
| Wash                      | No          |
| Iron                      | No          |
| Tumble dry                | No          |
| Bleach                    | No          |
| Dry clean                 | Yes         |
| Squeeze                   | No          |
| Keep away from direct sun | If possible |

|          |                                                                                                                                                                                                                |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Comments | <b>Tear resistance EN ISO 4674-2: width - 1.0kg / length - 2.3kg</b><br><b>Tensile strength EN ISO 1421: width - 24kg / length - 40kg</b><br><b>Tensile elongation EN ISO 1421: width - 17% / length - 14%</b> |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|